

# CONVERTIBLE AIR SPECIFICATIONS

MODEL	OACH1211	OACH1811	OACH2412	OACH3612	OACH3632	OACH6012	OACH6032	OACH6034
Cooling Capacity	12,700	18,010	24,020	36,050	36,050	60,050	60,050	60,050
Heating Capacity	11,685	15,850	21,380	32,445	32,445	53,445	53,445	53,445
Voltage	115/60/1 or 208/230/1		208/230/1		208/230/3	208/230/1	208/230/3	460/3
Cooling Amps	12.0/6.0	15.5/7.8	12.3	22.5	14.0	34.0	25.0	12.4
Heating Amps	12.0/6.0	15.6/7.8	12.4	20.0	13.6	34.7	25.6	12.5
Cooling Watts	1256	1590	2200	3360	3360	5900	5900	5900
E.E.R.	10.1	11.3	10.9	10.7	10.7	10.1	10.1	10.1
Heating Watts	1156	1400	1980	2290	2290	5330	5330	5330
C.O.P.	3.0	3.3	3.2	3.2	3.2	3.0	3.0	3.0
In Rush Current (AMPS)	92.8	114.2	79	128.8	111.8	198.0	134.2	135.6
Fuse/Breaker (AMPS)	15	20	20	30	20	50	40	30
Plug Type	5-15P	5-20P	6-20P	6-30P	L15-20P	6-50P	L15-30P	L16-30P
Compressor HP	1	1 1/2	2	3	3	5	5	5
Compressor RLA	9.3	11.4	8.3	17.9	11.4	28.0	20.0	8.2
Compressor LRA	58	65	49	88	77.0	169	123.0	59.6
Evaporator CFM	400	600	810	1310	1310	2200	2200	2200
Evap Motor HP	1/15	1/5	1/3	1/2	1/2	1	1	1
Evap Motor Watts	200	210	350	375	375	550	550	550
Condenser CFM	580	930	1010	1390	1390	2900	2900	2900
Condenser Motor HP	1/8	1/3	1/2	3/4	3/4	1	1	1
Condenser Motor Watts	280	450	330	460	460	750	750	750
Condensate Pump Head 20 Feet	Pump Optional on these models					Pump Standard on 5 ton		
Sound Level	54	60	65	69	69	78	78	78
R-22 Charge Oz.	29	42	40	45	45	68	68	68
Height with Casters	31 1/2	37 1/2		47		52 1/4		
Height without Casters	28 1/2	34 1/2		42 1/4		46 1/2		
Width	20 1/8	24 1/4		28 1/4				
Depth	22 5/8	24 3/4		31		39		
Net Weight	155	200	215	285	285	460	460	520
Shipping Weight	175	230	245	315	315	500	500	560
Shipping Volume	15	32	32	36	36	38	38	38

Cooling Capacity @ 80°F DB/67°F W.B. Indoor 95°F DB/75°F W.B. Outdoor Specifications subject to change without notice.

## CONVERTIBLE AIR available in 5 sizes: 1, 1.5, 2, 3 and 5 tons.

### FEATURES:

Room or discharge temperatures can be displayed on the LED window.

For very humid and cool areas, a moisture control mode can be used. This cycles the compressor and evaporator motor to reduce humidity levels without excessively lowering room temperature.

Easy to clean semi-gloss finish and heavy-duty steerable non-marring casters.

- Automatic (or manual) switching from cooling to heating modes
- 6-speed automatic (or manual) fan control system
- A thermostat set point range from 55° to 85°
- Backward curved motorized Impellers
- Built-in electronic hour meter