



Window Kit Available

STANDARD FEATURES

- Programmable 18-hour ON/OFF timer. This feature allows the unit to be programmed to start or stop automatically for a preset period of time (up to 18 hours).
- Washable air filter. Filter can be removed from unit and washed in warm water with a mild detergent eliminating the need for replacement filters.
- Built-in water reservoir with overflow alarm. Accommodates 3.8 liters (128-fl. oz.) of water. A back-up system, employing a visual/audible alarm prompt, suspends dehumidification when the reservoir is full to prevent overflow damage.
- Hot-air exhaust ducting kit with flat coupling is included with the P0811. When installed, hot air is dispersed through a duct tube mounted in an open window or through the wall. The ducting kit can be used with or without the flat coupling.
- 3-speed fan with horizontal auto-swing louvers. Enhance cooling and fanning performance and maximize energy efficiency to improve air circulation in poorly ventilated environments.
- Indoor use only.
- Silent operation (<51.5 dB). The P0811 operates "whisper quietly" minimizing distractions in the workplace and promoting a good night's sleep.

5-YEAR SANYO COMFORT WARRANTY

- During the first year, SANYO warrants the P0811 for all parts. To extend our commitment to product quality, SANYO will provide a "Compressor Only" warranty for an additional four years.

SPECIFICATIONS Performance and Electrical Rating

Cooling Capacity	7200 BTU/h @ 86°F/70% Humidity
Dehumidification (per day)	37.5 liters (1267 oz.)
Fan Control	Low-Med-High
Electrical	115V, 60Hz, 6.2A
Power Consumption	692W
Refrigerant	HCFC R22

Features:

Controls	Microcomputer
Thermostat Control	61°F~86°F
Filter	Washable
Operating Sound	<50dB-A
Timer	On/Off /18-hour

Dimensions:

Height	31"
Width	12 ⁷ / ₈ "
Depth	16 ³ / ₈ "
Net Weight	74lbs.